



Suria Master

PRODUCT SPEC SHEET

Quality Solar Barricade Lights

SUMMARY SPECIFICATIONS SHEET

SOLAR POWERED 360 DEGREE LIGHT

360ST / 360BX / 360SC TYPE D LIGHT



Flash Rate:	60+/- Times/Minute	Box Mount Material:	HDPE
Power:	Crystalline solar panel	Lens Diameter:	4 inches
Energy:	NiMH Rechargeable Battery	Lens Height:	4 3/4 inches
Illumination:	High Intensity LEDs	On/Off Switch:	Automatic on dusk, off dawn
Lens Material:	Polycarbonate	Security:	Security bolt tool included
Base Material:	Polycarbonate	Vandalism:	Replaceable solar panel shield
Stake Mount Material:	ABS	Attachments:	Hardware for most barriers
Screw Mount Material:	ABS	Colors:	Red, Amber, White. Custom colors available per request

Suria Master Type D Lights are designed to meet or exceed FAA Performance Spec: Advisory Circular No. 150/5370-G compliant.

SOLAR POWERED DUAL FUNCTION BARRICADE LIGHT

ORDF002 TYPE A & C LIGHT



Flash Rate:	60+/- Times/Minute	Base Height:	3 1/4 inches
Power:	Crystalline solar panel	Total Height:	12 inches
Energy:	NiMH Rechargeable Battery	Width:	8 inches
Illumination:	High Intensity LEDs	Depth:	3 inches
Effective Intensity:	Minimum 4 candela uni-directional	On/Off Switch:	Automatic on dusk, off dawn
Lens Material:	Polycarbonate	Security:	Security bolt tool included
Base Material:	Polypropylene	Vandalism:	Replaceable solar panel shield
Lens Width:	7 inches	Attachments:	Hardware for most barriers
Lens Height:	9 inches	Colors:	Amber, Red, Blue. Custom colors available per request
		Bolt Tool:	Glass Filled Nylon

Suria Master Type A & C Lights are designed to meet or exceed MUTCD requirements and ITE specifications. NCHRP-350 certified.

SOLAR POWERED HIGH INTENSITY BARRICADE LIGHT

ORBL006 TYPE B LIGHT



Flash Rate:	60+/- Times/Minute	Base Height:	4 1/2 inches
Power:	PET laminated solar panel	Total Height:	14 1/2 inches
Energy:	NiMH Rechargeable Battery	6 Hour Sun Charge:	14 days
Illumination:	9 High Intensity LEDs	Width:	8 1/2 inches
Effective Intensity:	Minimum 45 candela uni-directional	Depth:	4 3/4 inches
Lens Material:	Polycarbonate	On/Off Switch:	24 hr / 7 days a week operation
Base Material:	ABS	Security:	Security bolt tool included
Lens Diameter:	7 inches	Vandalism:	Replaceable solar panel shield
Lens Height:	9 3/4 inches	Colors:	Amber, Red. Custom colors per request.

Suria Master Type B Lights are designed to meet or exceed meet or exceed MUTCD requirements and ITE Specifications. NCHRP-350 certified.



Suria Master LLC

Tel: (800) 758-1758 • e-mail: sales@SuriaMaster.com

Web: www.SuriaMaster.com

Manufactured by: Solar Master SDN. BHD.